

POWERLINE

DIESEL GENERATING SET

YOUR TRUSTED GENSET COMPANY



SPECIFICATION GENSET	OPEN TYPE	SILENT TYPE
Model Genset	PL 500 CN	PL 500 CN
Power Output	500 kVa / 400 kW	500 kVa / 400 kW
Phase	3 (three)	3 (three)
Frequency	50 Hz @ 1500RPM	50 Hz @1500 RPM
Voltage	220/380 V	220/380 V
Control Panel	Deep Sea Module, Pilot Lamp Indicator, Emergency Stop Button, MCCB	Deep Sea Module, Pilot Lamp Indicator, Emergency Stop Button, MCCB
Accessories	Fuel Tank, Residential Muffler, Batteries, Tools Kit	Fuel Tank, Residential Muffler, Batteries, Tools Kit
Dimension LxWxT	3600 x 1500 x 2550 mm	5000 x 1800 x 2100 mm
Weight	4000 kg	5200 kg
Fuel Tank Cap (Ltr)	400	600

ENGINE	
Type	KTA19G4
Cooling System	Water Cooled with Radiator
Number of cylinders	6 vertical in-line
Cycle	4 stroke
Bore x Stroke	159 x 159 mm
Displacement	18.900 Liters
Total Lubrication cap	50 Liters
Fuel Consumption (L/H)	78.8 (75% Load) / 104 (100% Load)

GENERATOR	
Insulation System	Class H
Protection	IP 23
Rated Power Factor	0.8
Stator Winding	Double Layer Laps
Winding Pitch	Two Thirds
Winding Leads	12

Hubungi kontak dibawah untuk harga dan diskon terbaik :

PT. POWERLINE DIESEL INTI PRATAMA
 Pergudangan EHA, Jl Raya Legok KM.06 No.77
 Desa Carangpulang Tangerang, Indonesia.
 021 2222 7058
 info@powerline.co.id

