



DIESEL GENERATING SET

YOUR TRUSTED GENSET COMPANY



SPECIFICATION GENSET	OPEN TYPE	SILENT TYPE
Model Genset	PL 1250 CN	PL 1250 CN
Power Output	1250 kVa / 1000 kW	1250 kVa / 1000 kW
Phase	3 (three)	3 (three)
Frequency	50 Hz @ 1500RPM	50 Hz @1500 RPM
Voltage	220/380 V	220/380 V
Control Panel	Deep Sea Module, Pilot Lamp Indicator, Emergency Stop Button, MCCB	Deep Sea Module, Pilot Lamp Indicator, Emergency Stop Button, MCCB
Accessories	Fuel Tank, Residential Muffler, Batteries, Tools Kit	Fuel Tank, Residential Muffler, Batteries, Tools Kit
Dimension LxWxT	5650 x 2060 x 2330 mm	N/A
Weight	9800 kg	N/A
Fuel Tank Cap (Ltr)	OPT	N/A

ENGINE	
Type	KTA50-G3
Cooling System	Water Cooled with Radiator
Number of cylinders	16 vertical in-line
Cycle	4 stroke
Bore x Stroke	159 x 159 mm
Displacement	50.300 Liters
Total Lubrication cap	177 Liters
Fuel Consumption (L/H)	199 (75% Load) / 261 (100% Load)

GENERATOR	
Insulation System	Class H
Protection	IP 23
Rated Power Factor	0.8
Stator Winding	Double Layer Laps
Winding Pitch	Two Thirds
Winding Leads	12

Hubungi kontak dibawah untuk harga dan diskon terbaik :

PT. POWERLINE DIESEL INTI PRATAMA
 Pergudangan EHA, Jl Raya Legok KM.06 No.77
 Desa Carangpulang Tangerang, Indonesia.
 021 2222 7058
 info@powerline.co.id



www.powerline.co.id
 www.cumminsgenset.co.id
 www.servicegensetpowerline.com