

POWERLINE

DIESEL GENERATING SET

YOUR TRUSTED GENSET COMPANY



SPECIFICATION GENSET	OPEN TYPE	SILENT TYPE
Model Genset	PL 50 CN	PL 50 CN
Power Output	50 kVa / 40 kW	50 kVa / 40 kW
Phase	3 (three)	3 (three)
Frequency	50 Hz @ 1500RPM	50 Hz @1500 RPM
Voltage	220/380 V	220/380 V
Control Panel	Deep Sea Module, Pilot Lamp Indicator, Emergency Stop Button, MCCB	Deep Sea Module, Pilot Lamp Indicator, Emergency Stop Button, MCCB
Accessories	Fuel Tank, Residential Muffler, Batteries, Tools Kit	Fuel Tank, Residential Muffler, Batteries, Tools Kit
Dimension LxWxT	1900 x 750 x 1900 mm	2600 x 1000 x 1300 mm
Weight	883 kg	1301 kg
Fuel Tank Cap (Ltr)	70	100

ENGINE	
Type	4BTA3.9G2
Cooling System	Water Cooled with Radiator
Number of cylinders	4 vertical in-line
Cycle	4 stroke
Bore x Stroke	102 x 120 mm
Displacement	3.900 Liters
Total Lubrication cap	11 Liters
Fuel Consumption (L/H)	8.9 (75% Load) / 11.8 (100% Load)

GENERATOR	
Insulation System	Class H
Protection	IP 23
Rated Power Factor	0.8
Stator Winding	Double Layer Laps
Winding Pitch	Two Thirds
Winding Leads	12

Hubungi kontak dibawah untuk harga dan diskon terbaik :

PT. POWERLINE DIESEL INTI PRATAMA
 Pergudangan EHA, Jl Raya Legok KM.06 No.77
 Desa Carangpulung Tangerang, Indonesia.
 021 2222 7058
info@powerline.co.id

